








SCHEMATIC	
MODEL NO	F



Pin Hole Layout
(Jack Bottom View)



NUT



WASHER

9.	Nut	Low Lead Brass Rod	1	Nickel Plated
8.	Washer	0.4T Brass	1	Nickel Plated
7.	Tip Shunt	0.4T Brass	1	Silver Plated
6.	Tip Spring	0.4T Phosphor Bronze	1	Silver Plated
5.	Ring Shunt	0.4T Brass	1	Silver Plated
4.	Ring Spring	0.4T Phosphor Bronze	1	Silver Plated
3.	Sleeve Shunt	0.4T Brass	1	Silver Plated
2.	Barrel	Low Lead Brass Rod	1	Nickel Plated
1.	Housing	PA66	1	Black Color
NO.	Description	Material	Q'TY	Finish



S.C. PRECISION INDUSTRIAL CO., LTD.

DATE	DWN	CHKD	APVD	MANAGER
03.31.2022	王平華			

PART NAME : 6.3φ PHONE JACK

PART NUMBER: SCJ636R0NFS4BP0L

VERSION: 2.0

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT: mm



SCALE: 1/1

SPECIFICATIONS:

Contact Resistance : 30mΩ max
Insulation Resistance : 100MΩ min. at DC 500V
Dielectric Withstand Voltage : AC 500V for one minute
Remark: ▲: The Most Important Dimension

For Reference
僅供參考

RoHS&SVHC
Pb Free Process