










M12XP1.0
METRIC THREAD



11	Washer	0.5T Steel	1	Nickel Plated
10	Nut	2.0T Steel	1	Nickel Plated
9	Insulator	POM	1	Ivory Color
8	Insulator	Red Vulcanited Fibre	1	Red Color
7.	Bushing	Low Lead Brass Rod	1	Nickel Plated
6.	Barre(W/Thread)	POM	1	Black Color
5.	Cover	0.5T Steel	1	Nickel Plated
4.	Housing	POM	1	Black Color
3.	Tip Spring	0.35T Phosphor Bronze	1	Silver Plated
2.	Transfer Terminal	0.4T Brass	1	Silver Plated
1.	Break Terminal	0.35T Phosphor Bronze	1	Silver Plated
NO.	Description	Material	Q 'TY	Finish



S.C.PRECISION INDUSTRIAL CO., LTD.

DATE	DWN	CHKD	APVD	MANAGER
07.28.2021	王平華			

For Redference
僅供參考

RoHS&SVHC
Compliant

PART NAME : 6.3Ø PHONE JACK PART NUMBER: SCJ618R3NGS1B21L

VERSION: 1.0

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT: mm



SCALE: 1/1

SPECIFICATIONS:

Contact Resistance : 30mΩ max
Insulation Resistance : 100MΩ min. at DC 500V
Dielectric Withstanding Voltage: AC 500V for one minute
Remark: ▲: The Most Important Dimension