


15.	Insulator	POM	2	Black Color
14.	Transfer Terminal	0.35T Phosphor Bronze	1	Silver Plated
13.	Break Terminal	0.4T Brass	1	Silver Plated
12.	Break Terminal	0.4T Brass	1	Silver Plated
11.	Transfer Terminal	0.35T Phosphor Bronze	1	Silver Plated
10.	Washer	0.5T Steel	1	Nickel Plated
9.	Nut	2.0T Steel	1	Nickel Plated
8.	Cover	PBT+15%	1	Black Color
7.	Housing	POM	1	Black Color
6.	Barre	Low Lead Brass Rod	1	Nickel Plated
5.	Earth Spring	0.2T Phosphor Bronze	1	Nickel Plated
4.	Guide Plate	1.0T Bakelite	1	Natural
3.	Ring Terminal	0.25T Phosphor Bronze	1	Silver Plated
2.	Tip Terminal	0.35T Phosphor Bronze	1	Silver Plated
1.	Sleeve Terminal	0.5T Steel	1	Nickel Plated
NO.	Description	Material	Q'TY	Finish



S.C. PRECISION INDUSTRIAL CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
	03.22.2022	王平華			

For Redference
僅供參考

RoHS&SVHC
Compliant

PART NAME : 6.3φ PHONE JACK	PART NUMBER: SCJ628M2NCS3B00L	VERSION: 1.0
TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: /

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲: The Most Important Dimension