









8.	Washer	0.5T Steel	1	Nickel Plated
7.	Nut	2.0T Steel	1	Nickel Plated
6.	Housing	PBT	1	Black Color
5.	Barrel	Brass	1	Nickel Plated
4.	Ring Spring	0.4T Phosphor Bronze	1	Silver Plated
3.	Tip Spring	0.4T Phosphor Bronze	1	Silver Plated
2.	Tip Shunt	0.4T Brass	1	Silver Plated
1.	Earth Terminal	0.4T Brass	1	Silver Plated
NO.	Description	Material	Q 'TY	Finish



S.C. PRECISION INDUSTRIAL CO., LTD.

DATE	DWN	CHKD	APVD	MANAGER
10.12.2011				


PART NAME : 6.3 ϕ PHONE JACK

PART NUMBER: SCJ648M2NVS3B00G

VERSION: 2.0

TOLERANCE : $\pm 0.3\text{mm}$ UNLESS OTHERWISE SPECIFIED

UNIT: mm



SCALE: 1/1

SPECIFICATIONS:

Contact Resistance

: 30m Ω max

Insulation Resistance

: 100M Ω min. at DC 500V

Dielectric Withstanding Voltage: AC 500V for one minute

Remark: $\blacktriangle$: The Most Important Dimension

RoHS
Compliant

For Reference
僅供參考