






WASHER



NUT



$\phi 3/8 \times 32W$ PLASTIC BUSHING



6.	Washer	0.4T Brass	1	Nickel Plated
5.	Nut	2.2T Brass	1	Nickel Plated
4.	Housing	PBT	1	Black Color
3.	Tip Spring	0.4T Phosphor Bronze	1	Silver Plated
2.	Tip Shunt	0.4T Brass	1	Silver Plated
1.	Earth Terminal	0.4T Brass	1	Silver Plated
NO.	Description	Material	Q 'TY	Finish



S.C. PRECISION INDUSTRIAL CO., LTD.


DATE	DWN	CHKD	APVD	MANAGER
10.12.2011				

PART NAME : 6.3 ϕ PHONE JACK PART NUMBER: SCJ649P20YS4B00G

VERSION: 2.0

TOLERANCE : $\pm 0.3\text{mm}$ UNLESS OTHERWISE SPECIFIED

UNIT: mm



SCALE: 1/1

SPECIFICATIONS:

Contact Resistance : 30m Ω max
 Insulation Resistance : 100M Ω min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: $\blacktriangle$: The Most Important Dimension

RoHS
Compliant

For Reference
僅供參考