







SCHEMATIC	
MODEL NO	U



9.	Bushing	PBT+30%	1	Black Color
8.	Cover	PBT+15%	1	Black Color
7.	Housing	PBT+15%	1	Black Color
6.	Sleeve(Barrel)	Low Lead Brass Rod	1	Nickel Plated
5.	Tip Spring	0.3T YCuT	1	Silver Plated
4.	Break Terminal	0.4T Brass	1	Silver Plated
3.	Break Terminal	0.4T Brass	1	Silver Plated
2.	Ring Spring	0.3T Phosphor Copper	1	Silver Plated
1.	Earth Terminal	0.5T Steel	1	Tin Plated
NO.	Description	Material	Q'TY	Finish



	DATE				DWN	CHKD	APVD	MANAGER
	06.25.2021				王平華			

PART NAME : 3.5∅ PHONE JACK	PART NUMBER: SCJ356M5NUS0BB0L	VERSION: 1.0
TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1

SPECIFICATIONS:
Contact Resistance : 30mΩ max
Insulation Resistance : 100MΩ min. at DC 500V
Dielectric Withstanding Voltage: AC 500V for one minute
Remark: ▲: The Most Important Dimension

For Redference
僅供參考
RoHS&SVHC
Compliant