








SCHEMATIC

MODEL NO

1

Z



Pin Hole Layout
(Jack Bottom View)

6.	Bushing	PBT+30%	1	Black Color
5.	Cover	PBT+15%	1	Black Color
4.	Housing	PBT+15%	1	Black Color
3.	Sleeve(Barrel)	Low Lead Brass Rod	1	Nickel Plated
2.	Tip Spring	0.3T YCuT	1	Silver Plated
1.	Earth Terminal	0.5T Steel	1	Tin Plated
NO.	Description	Material	Q'TY	Finish



S.C.PRECISION INDUSTRIAL CO., LTD.

DATE	DWN	CHKD	APVD	MANAGER
06.25.2021	王平華			

PART NAME :3.5∅ PHONE JACK

PART NUMBER: SCJ356M5NZS0BB0L

VERSION:1.0

TOLERANCE :±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT:mm

SCALE:1/1

SPECIFICATIONS:
Contact Resistance : 30mΩ max
Insulation Resistance : 100MΩ min. at DC 500V
Dielectric Withstanding Voltage: AC 500V for one minute
Remark: ▲: The Most Important Dimension

For Redference
僅供參考

RoHS&SVHC
Compliant