


A部詳圖: (塑柱: 2/1)



10.	Housing	PBT	1	Red Color
9.	Housing	PBT	1	White Color
8.	Housing	PBT	1	Black Color
7.	Base	ABS	1	Black Color
6.	Contact Terminal D	0.5T Brass	1	Silver Plated
5.	Earth Terminal D (Barrel D)	0.5T Brass	1	Nickel Plated
4.	Contact Terminal C	0.5T Brass	1	Silver Plated
3.	Earth Terminal C (Barrel C)	0.5T Brass	1	Nickel Plated
2.	Contact Terminal T	0.5T Brass	1	Silver Plated
1.	Earth Terminal T (Barrel T)	0.5T Brass	1	Nickel Plated
NO.	Description	Material	Q'Ty	Finish

Pin Hole Layout
(Jack Bottom View)



DATE	DWN	CHKD	APVD	MANAGER
07.27.2009				

PART NAME : PIN JACK	PART NUMBER: SCP644CNS132000G	VERSION:3.0
TOLERANCE :±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT:mm	SCALE:1/1

SPECIFICATIONS:

Contact Resistance : 30mΩ max

Insulation Resistance : 100MΩ min. at DC 500V

Dielectric Withstanding Voltage: AC 500V for one minute

Remark: ▲: The Most Important Dimension

RoHS Compliant

For Reference 僅供參考